



For low drain / long term operating applications requesting good voltage response in  $-40^{\circ}\text{C}\sim+125^{\circ}\text{C}$  environments, such as TPMS(Tire Pressure Monitor System).

International size reference: 1/10D .

## Electrical characteristics

(Typical values for cells stored for one year or less, at  $25^{\circ}\text{C}$ )

● Nominal capacity		1.00Ah
(At 1.0mA, $+25^{\circ}\text{C}$ , 2.0V cut off. The capacity restored by the cell varies according to current drain, temperature and cut off voltage.)		
● Rated voltage		3.6V
● Maximum recommended continuous current		10mA
(To get 50% of the nominal capacity at $+25^{\circ}\text{C}$ with 2.0V cut off. Higher currents possible, consult EVE.)		
● Maximum pulse current capability		50mA
● Rated 1 sec.pulse capability(to 3V)		20mA
<b>Pulse capability</b> varies according to pulse characteristics (frequency duration), temperature, cell history (storage conditions prior to usage) and the application's acceptable minimum voltage.		
● Storage	(recommended)	$30^{\circ}\text{C}$ max
	(possible without leakage)	$-55^{\circ}\text{C}\sim+150^{\circ}\text{C}$
● Operating temperature range		$-55^{\circ}\text{C}\sim+125^{\circ}\text{C}$
(Operation at temperature different from ambient may lead to reduced capacity and lower voltage plateau readings.)		
● Typical weight		19g

### ⚠ WARNING:

Fire, explosion and severe burn hazard. Do not recharge, crush, disassemble, heat above  $150^{\circ}\text{C}$ , incinerate, or expose contents to water. Do not solder directly to the cell.

## ER32L65T

Lithium-thionyl Chloride  
(Li-SOCl<sub>2</sub>) Battery

### KEY FEATURES


- ✓ High and stable operating voltage
- ✓ High minimum voltage during pulsing
- ✓ Low self discharge rate (less than 1% after 1 year of storage at  $+25^{\circ}\text{C}$ )
- ✓ Stainless steel container
- ✓ Hermetic glass-to-metal sealing
- ✓ Non-flammable electrolyte
- ✓ Compliant with IEC 86-4 safety standard and EN 50020 intrinsic safety
- ✓ Non restricted for transport
- ✓ Underwriters Laboratories (UL) component Recognition (File Number MH 28717)

### MAIN APPLICATIONS


- ✓ Tire Pressure Monitor System
- ✓ Alarms and security devices
- ✓ Memory back-up
- ✓ Tracking systems
- ✓ Automotive electronics
- ✓ Professional electronics ... etc.

Note: Any representations in this brochure concerning performance, are for informational purposes only and are not construed as warranties either expressed or implied, of future performance.


## 1. DISCHARGE CHARACTERISTICS@+25°C




## 2. VOLTAGE VS. TEMPERATURE




## 3. CAPACITY VS. CURRENT



## 4. STORAGE CHARACTERISTICS



# ER32L65T



### AVAILABLE TERMINATIONS:

Suffix-/P Tinned Nickel Pins