


YFT Series - Valve Regulated Lead Acid Battery

YFT150-12

Data Sheet

Ideal for 48V systems or installation of racks 19 "and 23"

SPECIFICATIONS		
Nominal voltage	12	V
20-hr rate Capacity to 1.75VPC at 20°C	166,00	Ah
10-hr rate Capacity to 1.75VPC at 20°C	161,00	Ah
DIMENSIONS		
Length	548 (±1)	mm
Width	110 (±1)	mm
Height	286 (±2)	mm
(height over terminals)	286 (±2)	mm
Mass (typical)	46	kg
TERMINAL TYPE		
Bolt terminal	M6	
OPERATING TEMPERATURE RANGE		
Storage	-20°C a +50°C	
Charge	-15°C a +50°C	
Discharge	-15°C a +60°C	
STORAGE		
Capacity loss per month at 20°C (approx)	3	%
CASE MATERIAL		
Standard Option	ABS (UL.94:HB)	
Flame retardant option (FR)	ABS (UL94:V0)	
CHARGE VOLTAGE		
Float charge voltage at 20°C	13.65 (±1%)	V
	2.275 (±1%)	V/cell
Float Charge voltage temperature correction factor (for variations from the standard 20°C)	-3	mV/cell/°C
Cyclic (or Boost) charge at 20°C	14.5 (±3%)	V
	2.42 (±3%)	V/cell
Cyclic Charge voltage temperature correction factor (for variations from the standard 20°C)	-4	mV/cell/°C
CHARGE CURRENT		
Float charge current limit	Pas de limite	A
Cyclic (or Boost) charge current limit	41,50	A
MAXIMUM DISCHARGE CURRENT		
1 minute	950	A
SHORT-CIRCUIT CURRENT & INTERNAL RESISTANCE (according to EN IEC 60896-21)		
Internal resistance	N/A	mΩ
Short-Circuit current	N/A	A
IMPEDANCE		
Measured at 1 kHz	3,2	mΩ
PERFORMANCE & CHARACTERISTICS		
Refer to the technical manual	YFT	
DESIGN LIFE		
EUROBAT Classification: Standard Commercial	10	years
Yuasa design life @ 20°C	10	years
SAFETY		
Installation	Can be installed and operated in any orientation except permanently inverted	
Handles	Batteries must not be suspended by their handles (where fitted)	
Vent valves	Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.	
Gas Release	VRLA Batteries release hydrogen gas which can form explosive mixtures in air. Do not place inside a sealed container	
Recycling	YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations	



3RD PARTY CERTIFICATIONS

ISO 9001 - Quality Management Systems
 ISO 14001 - Environmental Management Systems
 EN 18001 - OHSAS Management Systems
 UNDERWRITERS LABORATORIES Inc.



STANDARDS

IEC61056



ALL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE
 Issue No.: V.0 / Issue Date: 20130517

